



Pos.105 | Schmiermittel/Lubricant | Art.Nr.29700744

3mm Hartauftrag (HB600) an der Stirnfläche und am Umfang des Bohrkopfgrundkörpers, sowie Bohrkopfarme seitlich, kreuzförmig auftragen.
Kanten der Bohrkopfarme ohne Hardoxleisten flächig schützen. Vorstehende Kanten des Diskenhalters außen und Grundkörper Außenräume mit Anlaufschrägen versehen und flächig schützen. Drahtelektrode DIN 8555-MSG 6-GZ-60

Weld on 3mm hard-facing onto front surface and circumference of base body and lateral crosswise onto crusher arms. Protect edges of crusher arms without hardox plates on full surface. Add chamfers on edges of disc mount and base body of bucket and protect on full surface with welding electrode DIN 8555-MSG 6-GZ-60

Wenn nicht anderweitig angegeben, sind metrische Schaltschrauben entsprechend den HERRENKNECHT-Anweisungen nach folgender Tabelle anzuziehen
Schrauben-Anzugsmomente in Nm
nach AA-HKAG-2.5-026
Reibungskoeffizient $\beta_{ges.} = 0,12$

If not defined otherwise, metric screws have to be tightened in accordance with the prescriptions from HERRENKNECHT in the following table
Screw tightening torques in Nm
following AA-HKAG-2.5-026
coefficient of friction $\beta_{tot.} = 0,12$

	5.6	8.8	10.9	12.9
M16	85	180	265	310
M20	165	360	520	600
M30	570	1250	1800	2100

Revision	Change	Date	Drawn	Date	Released

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. ISO 16016

Edges of undefined shape ISO 13715:2000
Geometrical product specification (GPS) EN ISO 1101:2013
Surface specifications according to EN ISO 1302:1992

Drawing type assembly
Project M-1939M
Machine type AVN1000X-11



www.herrenknecht.com

Name
CUTTERHEAD TOOL
BOHRKOPFWERKZEUG
DA1710-SLM-B70-STI-B55

Drawn	Date	Name	Scale	Material no.	Material	Weight/kg	Projection

Drawing number	Sheet	Revision	Format
4410-008.2-001-00	1/1	-	A3