



**3 FOOT SHORT HEAD
 SYMONS® CONE CRUSHER
 CLEARANCE DIMENSIONS**

TECHNICAL DATA

TD7-001

PAGE 5 OF
 PROPRIETARY CODE G

PREPARED BY: RLW
 APPROVED BY: RJM

DATE OF ISSUE
 12JAN59

Metso Minerals Engineering Department

REV: A
 DATE: 13SEP99

SEE TD7-001 PAGE 1 FOR FIGURE.

	DESCRIPTION	
A	MAIN FRAME FLANGE	2'-8 1/4"
B	MAIN FRAME FLANGE	2'-10 1/4"
C	MAIN FRAME FLANGE	2'-8 1/4"
D	MAIN FRAME CAP DIAMETER.....	21 1/4"
E	TO BOTTOM OF MAIN FRAME CAP	17 3/4"
F	TO TOP OF ADJUSTMENT RING.....	3'-5 5/8"
G	ADJUSTMENT RING MAXIMUM DIAMETER	6'-6 3/4"
H	TO END OF COUNTERSHAFT	6'-0 3/8"
J	CLEARANCE REQUIRED FOR REMOVING COUNTERSHAFT BOX ASSEMBLY	8'-1 7/8"
K	MAXIMUM HEIGHT TO TOP OF HOPPER	5'-9 3/8"
L	TO TOP OF FEED ADJUSTMENT POST	5'-10 1/2"
M	CLEARANCE REQUIRED FOR REMOVING BOWL ASSEMBLY	7'-8 1/4"
N	OVERALL HEIGHT OF BOWL ASSEMBLY	3'-2 3/4"
P	ADJUSTMENT CAP MAXIMUM DIAMETER	4'-11 3/4"
Q	CLEARANCE REQUIRED FOR REMOVING MAIN SHAFT ASSEMBLY	8'-4 1/4"
R	HEAD OR MANTLE MAXIMUM DIAMETER.....	3'-3"
S	OVERALL HEIGHT OF MAIN SHAFT ASSEMBLY	4'-10 5/8"
T	BOTTOM OF HEAD TO BOTTOM OF MAIN SHAFT	2'-1 1/8"
U	MAIN SHAFT MAXIMUM DIAMETER.....	9"
V	SPRING RING MAXIMUM DIAMETER.....	5'-8 3/4"